

**NELSON. TURF**  
Quality. Service. Guaranteed!



## 6100 Pro I Series

Nelson's **New** 6100 Pro I Top Adjust gear drive is designed for basic residential and light commercial applications and is a direct replacement for Hunter® PGP® rotor by simply unscrewing the existing riser from the PGP® can and replacing it with the 6100 Pro I riser.

The 6100 has full and part circle rotation. When the universal adjustment tool is inserted, it provides a range of adjustments from 40° to 360°.

### 6100

- Operating range: 30-70 psi
- Pop up height: 5½"
- Body height: 7 ¾"
- Unadjusted Radius: 30'-51'
- Discharge: 1.0 – 9.5 GPM
- Maximum pressure: 70 PSI
- 20 per box

**30'-51'**

# 6100 Pro I Series

## —features



- Riser fits in existing Hunter® PGP® cans – simply unscrew the existing riser from the PGP® can and replace with the 6100 riser
- 3/4" Inlet – Replaces all standard rotors
- Top Adjustment – no training necessary
- Full and Part circle rotation – provides a range of adjustments from 40° to 360°
- Rubber Cover – Seals out dirt and increases product durability
- Wide Selection of Nozzles – Provides flexibility in system design
- Right Position Start – Rotor rotates counter clockwise from fixed right start position
- NIR<sup>2</sup> feature (Nozzle Insertion/Radius Reduction) eliminates the need to remove the cap for nozzle adjustments
- Eight interchangeable Acu-Cover nozzles ranging from 1.0 to 9.5 gpm
- Seven optional low-angle nozzles (13°) for windy areas or for throwing under trees
- Universal Adjustment Tool and installation instructions included
- 5 year warranty on materials and workmanship

Pressure	Max Radius	Min Radius	Discharge	Precipitation Rate <sup>1</sup>		Nozzle Number	Pressure	Max Radius	Min Radius	Discharge	Precipitation Rate <sup>1</sup>			
				IN/HR■	IN/HR▲						BAR	kPa	m	m
20	30	23	1.0	0.21	0.27	4	1.4	138	9.2	6.9	3.8	0.23	5.4	6.8
35	31	23	1.4	0.28	0.35		2.5	242	9.5	7.1	5.3	0.32	7.1	8.9
50	34	26	1.7	0.28	0.35		3.5	345	10.4	7.8	6.4	0.39	7.2	9.0
20	33	25	1.2	0.21	0.26	5	1.4	138	10.1	7.5	4.5	0.27	5.4	6.7
35	37	28	1.6	0.23	0.28		2.5	242	11.3	8.5	6.1	0.36	5.7	7.1
50	38	29	1.9	0.25	0.32		3.5	345	11.6	8.7	7.2	0.43	6.4	8.0
20	32	24	1.4	0.26	0.33	6	1.4	138	9.8	7.3	5.3	0.32	6.7	8.3
35	38	29	1.9	0.25	0.32		2.5	242	11.6	8.7	7.2	0.43	6.4	8.0
50	40	30	2.3	0.28	0.35		3.5	345	12.2	9.2	8.7	0.52	7.0	8.8
20	38	29	2.2	0.29	0.37	7	1.4	138	11.6	8.7	8.3	0.50	7.5	9.3
35	40	30	2.7	0.33	0.41		2.5	242	12.2	9.2	10.2	0.61	8.3	10.3
50	41	31	3.1	0.36	0.44		3.5	345	12.5	9.4	11.7	0.70	9.0	11.3
35	38	29	3.1	0.41	0.52	8	2.5	242	11.6	8.7	11.7	0.70	10.5	13.1
50	42	32	4.0	0.44	0.54		3.5	345	12.8	9.6	15.1	0.91	11.1	13.8
65	43	32	4.6	0.48	0.60		4.6	449	13.1	9.8	17.4	1.04	12.2	15.2
35	42	32	4.2	0.46	0.57	9	2.5	242	12.8	9.6	15.9	0.95	11.6	14.5
50	47	35	5.4	0.47	0.59		3.5	345	14.3	10.8	20.4	1.23	12.0	14.9
65	48	36	6.3	0.53	0.66		4.6	449	14.6	11.0	23.8	1.43	13.4	16.7
35	42	32	5.4	0.59	0.74	10	2.5	242	12.8	9.6	20.4	1.23	15.0	18.7
50	48	36	6.8	0.57	0.71		3.5	345	14.6	11.0	25.7	1.54	14.4	18.0
65	49	37	8.0	0.64	0.80		4.6	449	14.9	11.2	30.3	1.82	16.3	20.3
35	42	32	6.4	0.70	0.87	11	2.5	242	12.8	9.6	24.2	1.45	17.7	22.1
50	48	36	8.1	0.68	0.84		3.5	345	14.6	11.0	30.7	1.84	17.2	21.4
65	51	38	9.5	0.70	0.88		4.6	449	15.6	11.7	36.0	2.16	17.9	22.3

**6000 PRO I SERIES**  
 Nozzle color ●  
 25° trajectory  
 (6000/6100 series only)

Pressure	Max Radius	Min Radius	Discharge	Precipitation Rate <sup>1</sup>		Nozzle Number	Pressure	Max Radius	Min Radius	Discharge	Precipitation Rate <sup>1</sup>			
				IN/HR■	IN/HR▲						BAR	kPa	m	m
20	26	20	0.9	0.26	0.32	4	1.4	138	7.9	5.9	3.4	0.20	6.5	8.1
35	33	25	1.3	0.23	0.29		2.5	242	10.1	7.5	4.9	0.30	5.8	7.3
50	34	26	1.5	0.25	0.31		3.5	345	10.4	7.8	5.7	0.34	6.3	7.9
20	26	20	1.1	0.31	0.39	5	1.4	138	7.9	5.9	4.2	0.25	8.0	9.9
35	33	25	1.4	0.25	0.31		2.5	242	10.1	7.5	5.3	0.32	6.3	7.8
50	35	26	1.7	0.27	0.33		3.5	345	10.7	8.0	6.4	0.39	6.8	8.5
20	26	20	1.4	0.40	0.50	6	1.4	138	7.9	5.9	5.3	0.32	10.1	12.6
35	33	25	1.9	0.34	0.42		2.5	242	10.1	7.5	7.2	0.43	8.5	10.6
50	36	27	2.3	0.34	0.43		3.5	345	11.0	8.2	8.7	0.52	8.7	10.8
20	31	23	2.5	0.50	0.62	7	1.4	138	9.5	7.1	9.5	0.57	12.7	15.9
35	35	26	3.1	0.49	0.61		2.5	242	10.7	8.0	11.7	0.70	12.4	15.4
50	37	28	3.5	0.49	0.61		3.5	345	11.3	8.5	13.2	0.79	12.5	15.6
35	32	24	3.2	0.60	0.75	8	2.5	242	9.8	7.3	12.1	0.73	15.3	19.1
50	38	29	4.0	0.53	0.67		3.5	345	11.6	8.7	15.1	0.91	13.6	16.9
65	39	29	4.7	0.60	0.74		4.6	449	11.9	8.9	17.8	1.07	15.1	18.9
35	34	26	3.9	0.65	0.81	9	2.5	242	10.4	7.8	14.8	0.89	16.5	20.6
50	37	28	4.9	0.69	0.86		3.5	345	11.3	8.5	18.5	1.11	17.5	21.8
65	40	30	5.7	0.69	0.86		4.6	449	12.2	9.2	21.6	1.29	17.4	21.7
35	33	25	5.1	0.90	1.12	10	2.5	242	10.1	7.5	19.3	1.16	22.9	28.6
50	39	29	6.4	0.81	1.01		3.5	345	11.9	8.9	24.2	1.45	20.6	25.7
65	42	32	7.5	0.82	1.02		4.6	449	12.8	9.6	28.4	1.70	20.8	25.9

**6095 LOW ANGLE**  
 Nozzle color ●  
 13° trajectory  
 (optional for 6000/6100 series only)

<sup>1</sup> Precipitation rates for square and triangular spacing calculated at 50% of diameter for half-circle operation. Assumes zero wind for precipitation and radius. Adjust for local conditions.